

LENNOX COMMERCIAL SMALL SPLIT SYSTEM UNITS

QUICK REFERENCE GUIDE



Features	Standard-Efficiency, Single-Stage Air Conditioner	Standard-Efficiency, Single-Stage Heat Pump	High-Efficiency, Two-Stage Air Conditioner	High-Efficiency, Two-Stage Heat Pump
Model Number	ML14XC1	ML14XP1	ML18XC2	SPB
Size (tons)	3-5	3-5	3-5	3-5
Voltage	208/230, 460, 575	208/230, 460	208/230, 460	208/230
SEER (up to)	16.0	16.0	18.0	17.0
HSPF (up to)	--	9.0	--	9.5
Stages of Cooling	Single-Stage Compressor	Single-Stage Compressor	Two-Stage Compressor	Two-Stage Compressor
Quiet Design (as low as)	76 dB	76 dB	76 dB	76 dB
Low ambient kit	Optional	Optional	Optional	Optional
Low ambient kit temperature	0°F	0°F	0°F	0°F
Scroll compressors	Yes	Yes	Yes	Yes
Condenser coil design	Quantum	Quantum	Quantum	Copper tube/Aluminum fin
Hi-capacity liquid drier	Furnished w/ unit for field installation	Yes	Furnished w/ unit for field installation	Yes
Crankcase heater	Yes	Yes	4-5 Ton Yes 3 Ton Optional	Yes
High-pressure switch	Furnished w/ unit for field installation	Yes	Yes	Yes
Low-pressure switch	Yes	Yes	Yes	Yes
Freezestat	Optional	Optional	Optional	Optional
Short-cycle protection	Optional	Yes	Optional	Yes