

# SUBMITTAL DATA - INDOOR UNIT

VSEC009S4-4P

## **Ductless Floor Standing**

Job:	Engineer:
Location:	Architect:
Schedule No.:	Location:
System Designation:	Date:
,	For: Reference Approval Review Construction
Floor Standing Indoor Unit /Evnos	

## Floor Standing Indoor Unit (Exposed)

#### **FEATURES**

- Easy Maintenance
- Advanced Commissioning and Service
- Refrigerant R-410A
- Five Capacity Sizes from 7,6000 to 24,000 Btu/h

#### WARRANTY

• 10-year limited warranty.\*See warranty for details.

SPECIFICATIONS		
PERFORMANCE		
Cooling Capacity <sup>1</sup> (Btu/h)		9,500
Heating Capacity <sup>1</sup> (Btu/h)		10,500
Airflow (CFM)	Low/Medium/High	160/195/250
External Static Pressure (in. w.	g.)	-
Sound (dBA)	Low/Medium/High	21/24/26
ELECTRICAL DATA		
Power Supply (Volts/Hertz/Pha	se)	208-230/60/1
Cooling Power Input (W)		40
Cooling Rated Current (A)		0.22
Heating Power Input (W)		40
Heating Rated Current (A)		0.22
Fan Motor Output (W)		10 x 1
DIMENSIONS		
Unit Dimensions (in)	Width	45.98
	Height	23.62
	Depth	8.66
Liquid Pipe Connection (in) (I.D.	0.)	1/4
Gas Pipe Connection (in) (I.D.)		1/2
Net Weight (lb)		57.3
Shipping Weight (lb)		65

OPTIONAL ACCESSORIES	
VSTAT02P-1 Touch Screen Wired Controller	37P79
VSTAT04P-1 Individual Wired Controller	37Y74
VSTAT01P-1 Wireless Remote Controller	37Y73



#### **NOTES**

- 1. Nominal capacity are based on (Refrigerant Piping : 25ft , Level Differences : 0ft);
- . Cooling : Indoor temperature : 80°F DB, 67°F WB / Outdoor temperature : 95°F DB, 75°F WB
- . Heating : Indoor temperature : 70°F DB, 60°F WB / Outdoor temperature : 47°F DB, 43°F WB
- 2. Sound pressure was acquired in a dead room. Thus actual noise level may be different depending on the installation conditions.
- 3. Specifications are subject to change without prior notice for product improvement.





## SUBMITTAL DATA - INDOOR UNIT

VSEC009S4-4P

**Ductless Floor Standing** 

### DIMENSIONAL DRAWINGS - MM (IN.)



