



COMMERCIAL TRAINING TOOLBOX TIPS

Pair the Model L Rooftop Unit to the Lennox CORE Service App

Applies to Lennox Model L and Enlight Rooftop Units 3-25 tons



Helpful Resources

1. Download installation and service literature from LennoxCommercial.com or LennoxPros.com.
2. [CORE Service App Reference Guide](#) takes you step-by-step through the startup and commissioning procedures.
3. Log in to LennoxPros.com to start the online [CORE Service Curriculum](#).
4. View [Lennox Model L and CORE Control System](#) videos on YouTube.

Required Tools

1. Download the CORE Service App to your mobile devices by scanning these QR codes.



You will need to pair your device to the Lennox CORE Control System to perform most setup, startup, or troubleshooting processes.

Open the CORE Service App on your device. Press the Pair button on the CORE Control System for 5 seconds.

See the excerpt from the [CORE Service App Reference Guide](#) below. Complete instructions are included in the guide.

1. This screen is displayed while the app is pairing to the unit.

Tap Next.

If prompted to allow the app to enable Bluetooth on your device, choose Accept.

2. Select the Proper RTU in the list shown to complete pairing to your device.

3. Once connected, the screen shown is a reading of the CORE controller's information.

Tap the Finish button to continue.

4. Congratulations! The unit and CORE Service App have been successfully paired!

The next screen is the unit operation overview screen.

Tap the Menu button. (3 lines in the upper left of the screen) to open the menu.

Self-Service Technical Support with No Wait Times
Click on the black logos below to download these apps

Download all [Training Toolbox Tips](#)
Register for [Technical Training Webinars](#)

