

SUBMITTAL DATA - INDOOR UNIT

VSEC024S4-4P

Ductless Floor Standing

Job:	Engineer:
Location:	Architect:
Schedule No.:	Location:
System Designation:	Date:
Floor Standing Indoor Unit /Evness	For: Reference Approval Review Construction

Floor Standing Indoor Unit (Exposed)

FEATURES

- Easy Maintenance
- Advanced Commissioning and Service
- Refrigerant R-410A
- Five Capacity Sizes from 7,6000 to 24,000 Btu/h

WARRANTY

• 10-year limited warranty.*See warranty for details.

SPECIFICATIONS			
PERFORMANCE			
Cooling Capacity ¹ (Btu/h)		24,000	
Heating Capacity ¹ (Btu/h)		27,000	
Airflow (CFM)	Low/Medium/High	390/495/550	
External Static Pressure (in. w.g	.)	-	
Sound (dBA)	Low/Medium/High	32/36/40	
ELECTRICAL DATA			
Power Supply (Volts/Hertz/Phas	e)	208-230/60/1	
Cooling Power Input (W)		110	
Cooling Rated Current (A)		0.53	
Heating Power Input (W)		110	
Heating Rated Current (A)		0.53	
Fan Motor U* qut (W)		F€Á¢ÁF	
DIMENSIONS			
Unit Dimensions (in)	Width	57.05	
	Height	23.62	
	Depth	8.66	
Liquid Pipe Connection (in) (I.D.)	3/8	
Gas Pipe Connection (in) (I.D.)		5/8	
Net Weight (lb)		69.4	
Shipping Weight (lb)		80.5	

OPTIONAL ACCESSORIES	
VSTAT02P-1 Touch Screen Wired Controller	37P79
VSTAT04P-1 Individual Wired Controller	37Y74
VSTAT01P-1 Wireless Remote Controller	37Y73



NOTES

1. Nominal capacity are based on (Refrigerant Piping : 25ft , Level Differences : 0ft);

. Cooling : Indoor temperature : 80°F DB, 67°F WB / Outdoor temperature : 95°F DB, 75°F WB

.Heating : Indoor temperature : 70°F DB, 60°F WB / Outdoor temperature : 47°F DB, 43°F WB

- 2. Sound pressure was acquired in a dead room. Thus actual noise level may be different depending on the installation conditions.
- 3. Specifications are subject to change without prior notice for product improvement.





SUBMITTAL DATA - INDOOR UNIT

VSEC024S4-4P

Ductless Floor Standing

DIMENSIONAL DRAWINGS - MM (IN.)



